

3152 DUAL ARRAY OF LPDA ANTENNAS

ETS-Lindgren's Model 3152 is a dual array of LPDA antennas based on the successful ETS-Lindgren Model 3148B.



ETS-Lindgren's Model 3152 is a dual array of LPDA antennas based on the successful ETS-Lindgren Model 3148B. With a frequency range of 200 MHz to 1 GHz, this antenna's array arrangement provides an additional gain improvement of 3 dB across the range, and a convenient space-saving design with the use of top hat-loaded, low-frequency elements. (Product photo shows Model 3152 mounted with Foreshortened Log Periodic Array mounted on a custom ETS-Lindgren positioning mast)

Key Features

- Pneumatically Driven Polarization
- 200 MHz to 1000 MHz Frequency Range
- Ideal for Immunity Testing Per 2004/144/EC and ISO-11451-2
- 1 kW Input Power Capability

Specifications

Electrical Specifications

Frequency Minimum: 200 MHz
Frequency Maximum: 1000 MHz
Input Impedance: 50 Ω
SWR: 1.5:1 Average, 2:1 Maximum
Maximum RF Input Power: 1 kW
RF Connector: N Type

Physical Specifications

Length: 3.6 m (11.81 ft)
Width: 1.0 m (3.28 ft)
Height: 1.0 m (3.28 ft)

Other Specifications

- Antenna
- Pedestal with Air Polarization (consult factory for details)